

Flowmeter

Silbermann flowmeter is a back-pressure compensated for all type of inhalation therapy

The flowmeter is unbreakable, with top cover and measuring tube made of clear transparent polycarbonate.



Oxygen flowmeter with probe

Rail mounted flowmeter



Features & Benefits

- Standard model flow rate: 0-15 LPM
- Low flow model flow rate: 0-7 LPM
- Both types with Oxygen DISS male outlet
- Non-linear scale enabling a clearer & accurate operation in the working range
- Different probes available
- Reliable, accurate and easy to use
- Non erasable laser engraved product info
- Rail mounted flowmeter includes:
1 meter plastic medical tubing, universal clamp and probe.



Technical Data

- Main Materials:
 - Body: Anodized Aluminum*
 - Cover: Transparent non-breakable polycarbonate.
 - Measuring tube: Transparent non-breakable polycarbonate

* Brass available on special request

Silbermann's Quality Management System:

- EN ISO 13485-2016
- ISO 9001-2015
- CE marked





Catalogue Numbers - Flowmeter with probe

Type of Male Adapter	0-15 LPM		0-7 LPM
	Oxygen Cat. No.	Air Cat. No.	Oxygen Cat. No.
Silbermann- Ohio	4110000	4148000	4107000
ENV 737-6	4110100	4148110	4107100
DIN 13260-2	4261000	4264000	4265000
Puritan Bennett type	4145000	4150000	4109000
BS5682	4110105	TBD	TBD
DISS	4112000	4147000	4134500
Without probe (1/8 NPT female thread)	4501100	4502100	4107010



Catalogue Numbers - Rail Mounted Flowmeter with probe

Type of Inlet\ Male Adapter	0-15 LPM		0-7 LPM
	Oxygen Cat. No.	Air Cat. No.	Oxygen Cat. No.
Silbermann- Ohio	4120001	4235000	4119001
ENV 737-6	4120101	4235005	4120110
DIN 13260-2	4233100	4235005	4225100
Puritan Bennett type	4233000	4237000	4225000
BS5682	TBD	TBD	TBD
DISS	4231000	4511000	TBD
Without probe (1/8 NPT female thread)	4120100	TBD	TBD

* Available on customer request



Related Products



Complete DISS metal nut assembly for Oxygen
P.N - 2229000



Oxygen DISS, plastic nut & gland, for one patient use
P.N - 2261000



Nebulizer*
P.N - 4103000



Humidifier*
P.N - 4101100



Bubble Jet
Humidifier/Nebulizer combo*
P.N - 4143000

* Silbermann's reusable Humidifiers/Nebulizers are made of polycarbonate tops, polysulfone jars and are autoclavable at 270°F (132°C).
Jars capacity - 500cc.
Includes safety valve 2 PSI
Inlet - DISS nut assembly.
Includes two flow outlets: 3 - 6mm bushed nipple & 22mm corrugated tube.
ISO color available on request



Assembly - Oxygen Unit



Rail Mounted Oxygen Unit



Oxygen Unit

Distributed By: